



### ***900 series from Romaco Noack***

All blister machines in the Romaco Noack 900 series can be supplied with either platen or rotary sealing. A balcony structure ensuring cGMP compliance together with integrated Track & Trace and containment solutions are the hallmarks of this technology. Servo and auto controls ensure precision execution independent of the operator.

#### **Highlights**

- QuickFeed – rapid tool free removal and replacement of feeding unit
- QuickAdjust – fast format part alignment and production start up
- QuickTransfer – precisely controlled placement of blister into the cartoner
- QuickAdmin – ergonomic operator panel
- QuickClean – cleaning concept
- QuickChange – quick product changes

Technical Data	Noack 930	Noack 960
Output blister/minute max.	400	700
Blister rows max.	4	6
Forming cycles/minute max.	100	100
Die-Cutting cycles/minute max.	120	120
Foil width max., in mm	165	235
Forming area max., in mm	155 x 180	225 x 180
Die-Cutting area max., in mm	155 x 140	225 x 140
Forming depth max., in mm	12	12
Forming foil reel diameter max., in mm	700	700
Lidding foil reel diameter max., in mm	300	400
Machine dimensions without transfer (L x W x H), in mm	5,100 x 1,600 x 2,200	6,600 x 1,600 x 2,100
Weight without transfer, in kg	3,500	4,500

